AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

- (currently amended) An insulative textile flooring pad comprising:
 reinforcement fibers; and
- binding fibers selected from the group consisting of polyethylene, polyester, polypropylene, and mixtures thereof, said pad having a density of greater than about [[13]] 10 pounds per cubic foot.
- 2. (original) The insulative textile flooring pad according to Claim 1 wherein the binding fibers and reinforcement fibers are distributed substantially randomly in a first plane.
- 3. (original) The insulative textile flooring pad according to Claim 1 comprising less than about 20% binder fiber.
- 4. (original) The insulative textile flooring pad according to Claim 1 comprising about 15% binder fiber.
- 5. (original) The insulative textile flooring pad according to Claim 1 comprising less than about 0.2 pounds per square foot binder fiber.

- 6. (original) Th insulative textile flooring pad according to Claim 4 comprising about 0.1875 pounds per square foot binder fiber.
- 7. (original) The insulative textile flooring pad according to Claim 1 comprising less than about 1.2 pounds per square foot reinforcement fiber.
- 8. (original) The Insulative textile flooring pad according to Claim 1 having a density of about 18.9 pounds per cubic foot.
 - 9. (original) A floor structure comprising:a sub floor;
 - a surface layer; and
- an insulative pad disposed between said sub floor and surface layer comprising binder and reinforcement fibers distributed substantially random in a first plane, said binder fibers being meltable at a predetermined temperature to couple the binding fibers to the reinforcement fibers.
- 10. (original) The floor structure according to Claim 9 wherein said surface material comprises wood.
- 11. (original) The floor structure according to Claim 9 wherein said surface material comprises ceramic.

- 12. (original) The floor structure according to Claim 9 wh rein the binder fibers are selected from the group consisting of polyethylene, polyester, polypropylene, and mixtures thereof.
- 13. (original) The floor structure according to Claim 9 having a density of greater than about 13.3 pounds per cubic foot.
- 14. (original) The floor structure according to Claim 9 having a density of about 18,9 pounds per cubic foot.
- 15. (original) The floor structure according to Claim 14 being about 3/32 inch thick.
- 16. (original) The floor structure according to Claim 9 having a compression resistance at a compression of 25% of the original thickness of greater than about 20 psi.
- 17. (original) The floor structure according to Claim 9 having a compression resistance at 50% of the original thickness of greater than about 180 psi.

(e

18. (currently am nded) A floor underlayment for disposal under a floor surface comprising:

less than about 20% thermoplastic binder fibers and more than about 80% reinforcement fibers;

said floor underlayment having a first surface disposed beneath said floor surface and having a density of greater than about [[13.3]] 10 pounds per cubic foot.

- 19. (original) The floor underlayment according to Claim 18 having a density of greater than about 18 pounds per cubic foot.
- 20. (original) The floor underlayment according to Claim 18 wherein the thermoplastic binder fiber is selected from the group consisting of polyethylene, polyester, polypropylene, and mixtures thereof.